



AMP2120 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Rack mounted system
Ultra-broadband MMIC hybrid design
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 20.0 GHz	
Power Output CW	20 Watt Min	CW
Power Output @ P1dB	8 Watt Typ	
Power Gain	43 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	33dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	-20 dBc Typ	At rated Pout
Non-Harmonic Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	300 Watt Max	At rated Pout
Max Input Power Protection	+3 dBm	Without damage
Load VSWR Protection	5 : 1	<10 Sec without damage

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 562 mm	3U, excluding handles
Weight	20 Kg.	
RF Connectors In/Out	Hi Freq. SMA-F / SMA-F	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Controller will reduce output power by up to 1.5dB.

AMP2120 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

