

AMP2056 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Small form factor, rack mounted system
Class A/AB Linear HF Amplifier design
High Power Advanced technology devices
Instantaneous ultra-wide bandwidth
Designed for EMI/RFI, lab, CW/Pulse and all communication applications
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	1.6 - 32 MHz	
Power Output	1000 Watt Min	CW or Pulse
Power Output @ P1dB GCP	>800 Watt Typ	
Power Gain	60 dB Min	0dBm or less for rated Pout
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	
Input Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	50dBm/Tone, Δ = 1MHz
Harmonics	2 nd	-20 dBc Typ
	3 rd	-13 dBc Typ
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	180 - 240 VAC	47-63 Hz
Power Consumption	2200 Watt Max	At rated Pout
Input Power Protection	+10 dBm Max ¹	
Load VSWR Protection	4 : 1: Max ²	Foldback @ preset limit
Sample Port (optional)	-60 dB	N-Female

1 Units with optional digital monitor and control, for basic units <10 Sec without damage

2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	483 x 178 x 560 mm	4U, excluding handles
Weight	30 Kg.	
RF Connectors In/Out/Sample	Type-N Female	Front or rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	IEC 60320-C14	Or equivalent
Safety Interlock Connector	D-Sub (Optional BNC female)	Open=STBY/Short=RFON
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	

e

AMP2056 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING
SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER

