



AMP2001A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Small form factor, light weight benchtop system
Class AB linear LDMOS design
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	1 - 1000 MHz	
Power Output@ Psat	20 Watt Min / 25 Watt Min	CW
Power Gain	44 dB Min	0dBm or less for rated Pout
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	
Input Return Loss	10 dB Min	
2-Tone Intermodulation (IMD)	-30 dBc Typ	34dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	150 Watt Max	At rated Pout
Max Input Power Protection	+8 dBm	<10 Sec without damage
Load VSWR Protection	∞ : 1	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ¹	

1 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	265 x 88 x 229 mm	2U, excluding handles
Weight	8 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	

e

AMP2001A SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

