

AMP20216

SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse, and all EW communication applications
 Small form factor system
 Class A/AB Linear design
 High-power advanced technology devices
 Instantaneous ultra-wide bandwidth
 Built-in protection circuits, with extensive monitoring
 Local LCD & remote flexible interfaces
 High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	0.7 – 6.0 GHz	
Power Output @ Psat	15 Watt Min	CW
Power Gain	42 dB Min	
Power Gain Flatness	4.5 dB p-p Max	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	37dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	-13dBc Typ in band
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 – 240 VAC	
Power Consumption	150 Watt Max	At rated output
Input Power Protection	+5 dBm Max ¹	
Load VSWR Protection	4:1 Max ²	Foldback @ preset limit

¹ Units with optional digital monitor and control, for basic units <10 Sec without damage

² Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

³ MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D (with Option DMC)	430 x 133.3 x 560 mm	3U, excluding handles
Dimensions W x H x D (Benchtop)	210 x 100 x 300 mm	Excluding brackets
	242 x 110 x 384 mm	Including brackets
Weight	(2U/9 kg.) (3U/12kg.)	
RF Conn. In / Out / Sample	SMA-Female	Front or rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	IEC 60320-C14	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control (DMC ⁴) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

⁴ Option DMC - LCD Controller option may reduce output power by 0.5 dB typical. Please consult the factory for more information.


AMP20216 SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-40dB, Type SMA-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type SMA-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	11-points standard ⁵

⁵ Consult with factory if additional points would be required.

OUTLINE DRAWING SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER



AMP20216 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING
2U, Benchtop (No display with DMC)

